

Real-Time Hatching

Emil Praun

Princeton

Hugues Hoppe

University

Matthew Webb

Microsoft Research

Adam

Princeton

Finkelstein

University

Princeton


University

Goal

Stroke-based rendering of 3D models


Strokes convey:

- tone
- material
- shape




Challenges

Interactive camera and lighting control
Temporal (frame to frame) coherence
Spatial continuity
Artistic freedom





Approach



Previous Work

Off-line
~~Real Time~~ Hatching



[Winkenbach *et al.* '94, '96] Hertzmann *et al.* 2000]



& many others ...

[Sousa *et al.*
'00]

Previous Work

NPR

~~Real-Time Hatching~~

- Technical Illustration

[Gooch *et al.* '99]

- Graftals



[Kowalski *et al.*

- Silhouette rendering

[Markosian *et al.* '97]

[Hertzmann *et al.* 2000]


[Sander *et al.* 2000]




Previous Work

Real-Time Hatching

- Screen-space “filter”
[Lake *et al.* 2000]




- Fixed density strokes
[Elber '99]




Previous Work – Stroke Collections

Prioritized Stroke Textures
[Salisbury *et al.* '94]
[Winkenbach *et al.* '94]




← tone →



Art Maps
[Klein *et al.* 2000]

← scale →




Tonal Art Maps

Collection of stroke images


Will blend → design with high coherence

Stroke nesting property

demo



Approach




Generating Tonal Art Maps

Draw or import bitmap for one stroke

Automatically fill TAM with strokes


- When placing stroke in an image, add it to all finer & darker images
- Fill table column by column, coarse to fine
- Space strokes evenly



Even Spacing of Strokes

Choose best stroke from large candidate pool


Fitness = uniformity & progress towards tone



Even Spacing of Strokes

Choose best stroke from large candidate pool


Fitness = uniformity & progress towards tone



Even Spacing of Strokes


Choose best stroke from large candidate pool

Fitness = uniformity & progress towards tone



Keep Gaussian pyramid for all TAM images

Approach




Continuity

Stroke size continuity → mipmapping

Tone continuity → blend multiple textures


- Spatial continuity: same contribution for a texture on both sides of an edge




spatial discontinuity

- Temporal continuity: no “popping” demo

Texture Blending



6-way blend \rightarrow *final*



Texture Blending

Pack grayscale tones in R,G,B channels

→ 6 tones in 2 textures

Use multitexture engine


→ single-pass 6-way blend

Vertex programs compute blend weights

→ static vertex data


```
!!VP1.0 #Vertex Program for Real-Time Hatching. //apply clamp-linear tone transfer function
//output vertex homogeneous coordinates
DP4 R2.x, c[0], v[OP0S];
DP4 R2.y, c[1], v[OP0S];
DP4 R2.z, c[2], v[OP0S];
DP4 R2.w, c[3], v[OP0S];
MOV o[HPOS], R2;
//stroke texture coordinates, transformed
DP3 o[TEX0].x, c[4], v[TEX0];
DP3 o[TEX0].y, c[5], v[TEX0];
DP3 o[TEX1].x, c[4], v[TEX0];
DP3 o[TEX1].y, c[5], v[TEX0];
// splotch mask coordinates
MOV o[TEX2], v[TEX0];
//get the Gouraud shade
DP3 R1, c[8], v[NRML];
MUL R1, R1, c[9].x;
ADD R1, R1, c[9].y;
MAX R1, R1, c[9].z;
MIN R1, R1, c[9].w;
//now look up the weights for the TAMs blending
EXP R2.y, R1.x; //frac(tone)
ARL A0.x, R1.x;
MOV R3, c[A0.x + 10];
MAD R3, -R2.y, R3, R3;
MAD o[COL1], R2.y, c[A0.x + 11], R3;
MOV R4, c[A0.x + 20];
MAD R4, -R2.y, R4, R4;
MAD o[COL0], R2.y, c[A0.x + 21], R4;
END
```

Approach



Texturing Arbitrary Surfaces

Lapped Textures
[Praun et al. 2000]




Direction Field

Based on surface principal curvatures

Optimized to be smooth


- [Hertzmann & Zorin 2000]
- Symmetry: 180° instead of 90°
- Sample on faces



Demo








Demo



Gargoyle

Demo



← *chalk*
→

gray

charcoal

Venus

Summary

Real-time hatching for NPR

Strokes rendered as textures

High coherence TAMs prevent blend artifacts


6-way blend very fast on modern graphics

Future Work

More general TAMs

View-dependent stroke direction

Automatic indication



Bill Plympton

Acknowledgements

Support

Microsoft Research, NSF

Hardware

NVidia, Dell

Models

Viewpoint, Cyberware, Stanford, MIT

Thanks

Georges Winkenbach, Lee Markosian, Grady Klein

NPAR 2002

International Symposium on Non-Photorealistic Animation and Rendering

- Annecy, France
- Submissions: November 12, 2001
- Conference: June 3-5, 2002

<http://npar2002.cs.princeton.edu>